CONSOLIDATED STERILIZER SYSTEMS

Choosing the Right WaterEco® System for Your Autoclave

Start Here

Do you want to minimize autoclave water consumption on an existing autoclave or a new autoclave?

- **EXISTING** → SOLUTION: WaterEco Basic Retrofit Kit (Saves up to 90%)
- **NEW** ↓

Does your facility have a chilled water loop near the autoclave and does it meet the minimum capacity requirements? (see table)

- **NOT SURE** → Check with your facilities department & refer to table
- **YES** ↓

Will your autoclave have a vacuum system* to run pre-vacuum cycles or vacuum drying?

- **YES** ↓
  - SOLUTION 1 : WaterEco Vac Plus**: Full Recirculation System With Liquid Ring Pump (Saves up to 99%)
  - SOLUTION 2 : WaterEco Plus With Liquid Ring Pump (Saves 50-70%)
- **NO** ↓
  - SOLUTION: WaterEco Plus (Saves up to 99%)

- **NO** ↓

Will your autoclave have a vacuum system* to run pre-vacuum cycles or vacuum drying?

- **YES** ↓
  - SOLUTION: WaterEco Basic With Liquid Ring Pump (Saves up to 75%)
- **NO** ↓
  - SOLUTION: WaterEco Basic (Saves up to 90%)

* Autoclaves with vacuum systems consume more water

**May require an additional footprint next to the autoclave

Chilled Water Requirements

Chilled Water Feed

20 psi dynamic min,
35F-50F max temperature,
10 GPM capacity

Chilled Water Return

-5 psi drop on return side, +15F max rise

3 ENTERPRISE RD, SUITE C | BILLERICA, MASS 01821
P: 617.782.6072 | **F:** 617.787.5865 | INFO@CONSTERIL.COM | **CONSTERIL.COM**

Featuring Green Technology for Energy Savings and Minimal Environmental Impact

Made in the U.S.A.

©2019 Consolidated Machine Corporation V1 7/19